

Connection components - fiber optic cabling

900 µm pigtail terminated with LC PC connectors



DESCRIPTION:

- pre-connectorized 900 µm buffer cable with LC PC connectors
- available with different type of SM fibers: G652D, G657A1, G657A2, G655
- customized length
- as a standard pigtails are produced with easy strip buffer that significantly speeds up assembly work
- available in set (6 or 12 pcs) or individually packed

TECHNICAL SPECIFICATION:

Parametr	LC PC
IL_{max} Acc. IEC 61300-3-4	≤ 0.17 dB
IL_{typ} Acc. IEC 61300-3-4	≤ 0.15 dB
RL against MASTER Acc. IEC 61300-3-6	≥ 55 dB

ORDERING INFORMATION:

G-LC-XX-S-AAA.A-P9-B-09-Y Syntax order for LC pigtails

AAA.A – length 1-100m, length tolerance L + 0.1/-0 m

B- fiber type; A – G652D, B – G655, D- G657A1, E – G657A2

Example:

G-LC-XX-S-002.0-P9-D-09-Y Fibrain pigtail LC PC SM 09/125 G657A1 yellow 2m length

Important notice

Buyer and/or user of this product has to make sure before using this product that it is suitable for the intended use. All questions of liability relating to this product are subject – in accordance with the prevailing – to the Term of Sale of the selling Fibrain subsidiary.