

PST patch panel, equipped



**DESCRIPTION:**

- Equipped PST patch panel:
  - 24x LCdx FO adapter
  - 48x LC PC SM G657A1 pigtail, 2m length
  - 2x SCM-A-24 splice tray
  - 48x splice protector 45mm
- Full opening on telescopic rails
- Internal perforation to manage tubes or fibers
- Optional front organizer for patchcords management
- Holder for the strength element of cable

**TECHNICAL SPECIFICATION**

Technical data	PST-B1
Height	1U
Width	19"
Depth	258 mm
Casing material	powder coated steel
Adapter capacity	24
Splice trays capacity SCM-A-24H	1
Connector type	LC PC
Pigtails length	2m
Fiber type	G657A1
IL <sub>max</sub> (IEC 61300-3-4)	≤ 0.20 dB
RL (IEC 61300-3-6)	≥ 55 dB

Internal view of the PST patch panel



**ORDERING INFORMATION**

**PST-A1-B1030-24151-48D02G01-12-481-11** Fibrain PST patch panel, 24x LC dx, 48 pigtails LC G657A1, splice trays, cable gland PG13.5mm

**Important notice**

Buyer and/or user of this product has to make sure before using this product that it is suitable for the intended use. All questions of liability relating to this product are subject – in accordance with the prevailing – to the Term of Sale of the selling Fibrain subsidiary.